

Model: H190BB - Standard Weight

STANDARD FEATURES

- Full mortise type hinge, standard weight, five knuckle, two ball bearings (2BB)
- UL/cUL Listed for 3 hours fire rating
- Conforms to ANSI/BHMA A156.1
- Meets ANSI/BHMA A156.7 requirements for template hinge dimensions
- Stainless steel leaf, pin, bearings, head and screws
- Standard 304 stainless steel
- Packed with machine screws (12-24 X 1/2" FHMS) and wood screws (12 X 1-1/4" FHWS)
- Finish: US32 (629) bright stainless steel, US32D (630) satin stainless steel
- Warranty: Limited 10 years



OPTIONAL FEATURES

- 316 stainless steel
- NRP Non removable pin

HINGE SIZES

MODEL	SKU	SKU WITH (NRP)	SIZE	FINISH	BALL BEARINGS
H190BB	H190BB-4030	H190BB-4030-NRP	4.0" X 3.0" X .123" (3.1mm)	- US32 (629) Bright stainless steel - US32D (630) Satin stainless steel	2 BB
	H190BB-4035	H190BB-4035-NRP	4.0" X 3.5" X .123" (3.1mm)		
	H190BB-4040	H190BB-4040-NRP	4.0" X 4.0" X .123" (3.1mm)		
	H190BB-4540	H190BB-4540-NRP	4.5" X 4.0" X .123" (3.1mm)		
	H190BB-4545	H190BB-4545-NRP	4.5" X 4.5" X .123" (3.1mm)		
	H190BB-5030	H190BB-5030-NRP	5.0" X 3.0" X .123" (3.1mm)		
	H190BB-5035	H190BB-5035-NRP	5.0" X 3.5" X .123" (3.1mm)		
	H190BB-5040	H190BB-5040-NRP	5.0" X 4.0" X .123" (3.1mm)		

