

## Models: H150SP/H151SP - Single Acting Spring Hinges

### FEATURES

- Used for medium frequency, standard weight doors, in place of door closers
- Full mortise single acting spring hinge, three knuckle, and anti friction nylon bearings
- Non-handed
- Adjustable spring tension
- UL/cUL listed for 3 hours fire rating
- Conforms to ANSI/BHMA A156.1
- Meets ANSI/BHMA A156.7 requirements for template hinge dimensions
- **H150SP:** Steel leaf and steel components
- **H151SP:** 304 Stainless steel leaf and inner parts
- Packed with machine screws (12-24 X 1/2" FHMS), wood screws (12 X 1-1/4" FHWS), and spring tensioner
- Radius corners (Optional)
- Finishes:
  - H150SP:** US3(605), US10B(613), US15(619), US19(622), US26(625), US26D(626)
  - H151SP:** US32(629), US32D(630)
- Warranty: Limited 10 years



### HINGE SIZES

MODEL	SKU	SIZE	FINISH
H150SP	H150SP-4040	4.0" X 4.0" X .130" (3.3mm)	- US3 (605) Bright brass clear coated - US10B (613) Dark satin bronze
	H150SP-4540	4.5" X 4.0" X .134" (3.4mm)	- US15 (619) Satin nickel plated - US19 (622) Matt black coated
	H150SP-4545	4.5" X 4.5" X .134" (3.4mm)	- US26 (625) Bright chrome plated - US26D (626) Satin chrome plated
H151SP	H151SP-4040	4.0" X 4.0" X .130" (3.3mm)	- US32 (629) Bright stainless steel - US32D (630) Satin stainless steel
	H151SP-4540	4.5" X 4.0" X .134" (3.4mm)	
	H151SP-4545	4.5" X 4.5" X .134" (3.4mm)	